
## 034.EOE.150K50L







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	150 g
Linearity:	100 g
Readability [d]:	50 g
Recommended adjusting weight:	100 kg (M2)
Repeatability:	50 g
Resolution:	3000
Tare range:	150 kg
Warm up time:	10 min
Weighing capacity [Max]:	150 kg
Weighing system:	Strain gauge
Weighing units:	lb PCS kg

Display		
Display digit height (large):	2,500 cm	
Functions		
Data hald function:	V00	

Functions		
Data hold function:	yes	
Vibration-free weighing (Animal	yes	
weighing program):		

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C

Power supply	
Battery:	4x1.5 V AA
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH US UK
Operating time:	100 h

## Services (optional)

Adjustment at the location of installation: 961-249

**DAkkS Certificate:** 963-129

Category **KERN** Brand: Category: Balances

Packaging & shipping

Delivery: 24 h

Dimensions packaging (WxDxH): 660 x 600 x 90 mm

Gross weight: 15,300 kg Net weight: 13,800 kg Shipping method: Parcel service

Construction	
Cable length of display device:	2 m
Casing material:	plastic
Dimensions of display device (WxDxH):	235 x 114 x 51 mm
Dimensions of weighing plate (WxDxH):	550 x 550 x 58 mm
Material weighing plate:	Steel lacquered
Wall mount:	yes

## Piktogramme

## STANDARD















**OPTION** 

