

# PR125/325/525

## PRESSURE LOGGER WITH DISPLAY

One-step data retrieval for utility operators on-the-go!-- retrieve data without the bother of moving data loggers or laptops. Easy-to-See, Easy-to-Download Data--

- Display with Min/Max option, Unit of Measure Indicator, Low battery Indicator and much more.
- USB-enabled triple speed downloading
- 1-second sampling rate
- IP68 case
- FLASH card option

User-friendly DicksonWare™ software makes it simple to integrate recorded pressure data into documents and spreadsheets, giving results a professional, polished look. When fulfillment of regulatory requirements or accurate recording of pressure for quality control is needed, this logger is the perfect instrument.



### Specifications:

**Pressure Ranges:** PR125: 0-100 PSI; PR325: 0-300 PSI; PR525: 0-500 PSI

**Accuracy:** ±1% of full scale

**Ambient Operating Conditions:** -22 to +176°F (-30 to +80°C) 0 to 100% RH

**IP Rating:** IP68

**Units of Measure:** Via DicksonWare: PSI, ATM, Bar, mBar, InH2O, FtH2O, mmH2O, mmHG, InHg, Pascal, kP, MCA

Via Display: PSI, ATM, mBar, InH2O, kP, MCA, BAR

**Approvals:** CE

**Battery Type:** 1 DL123 Lithium Battery (User Replaceable)

**Battery Life:** 6 months at 5 Minute Sample Rate

**Fitting:** 1/4" NPT Thread, 5/8" Hex

**Sample Point Storage:** 60,000 points

**Sample Interval:** User selectable from 1 second to 24 hours

**Download Time:** Approximately 1 minute with logger full

**Download Type:** USB or Flash Memory Card

**Enclosure:** Glass filled Polycarbonate; Stainless Steel Hex

**Dimensions:** 3.4" DIA x 2.8" H (8.64cm DIA x 7.11cm H)

**Weight:** 10.7 oz (300.7 g)

### A016 - DicksonWare™ & Download Cable Specifications:

**Compatible With:** Microsoft Windows® 98 or better

**Cable Type/Length:** USB male series "A" plug to 5-pin male series "B" mini plug, 6' (2 meters)

**Computer Interface:** USB

**DicksonWare™ Version Required (minimum):** v12.4